

Novaflex®

Thermoplastic Urethane Duct

TPUX

This duct's special molecular bonded construction means less turbulence for maximum flow efficiency. This lightweight, flexible duct will perform under the toughest conditions including low temperatures, oil and ozone and fungus. It is extremely flexible with excellent shape retention and is highly compressible for easier storage and transportation. Constructed without wire.

Novaflex TPUX offers

- Maximum abrasion resistance
- Superior tear resistance and high tensile strength
- Clear construction for visual monitoring
- Excellent low temperature flexibility
- Good chemical resistance, food grade

Specifications

Temperature range: -65°F (-54°C) to +200°F (+93°C)

Lengths: 25 & 50 ft

Sizes: 1" to 12" and half inch sizes: 1½", 2½", 3½", 4½" and 5½".

Compression ratio: 2:1

Clear with clear helix. White helix also available.

FDA material



Specification Chart

Size ID (in)	Min in. for 90° Bend	Bend Radius	Friction Loss Straight Run 100' (in Wg)	Friction Loss 90° 100' (in Wg)	Positive W. P. (PSIG)	Neg. W.P. (vacuum rating in Hg)	Wgt (per foot)	Crush Tests ½ ID (lbs per foot)
2"	9.5"	3.0"	1.72	1.84	22	29	0.44	780
3"	10.0"	3.5"	1.62	1.74	20	29	0.47	660
4"	11.5"	4.0"	1.29	1.42	18	26	0.56	510
5"	13.5"	5.0"	1.19	1.3	18	21	0.7	400
6"	14.5"	5.5"	1.17	1.28	16	16	0.84	350
8"	19.0"	7.0"	0.74	0.75	16	6	1.12	310
10"	21.0"	8.5"	0.71	0.73	14	5	1.24	270
12"	23.0"	9.5"	0.68	0.7	14	4.5	1.37	265

The above data is provided as a general guide only. Friction loss through flexible ducting is dependent on the diameter, length, values, inner wall surface, general duct construction and number of bends. Friction loss values were obtained using 100 ft straight runs with an air velocity of 3,500 FPM.

The information provided within is for informational purposes only. We have made every effort to ensure the accuracy of the provided information and assume no responsibility for any loss or damage due to errors or omissions or to the use or misuse of any information supplied. It is impossible to test all products under all conditions to which they might be subjected in the field. It is therefore the buyer and/or end users' responsibility to test all products under the conditions that duplicate the service conditions prior to installation. All improvements, all specifications are subject to change without prior notice. It is the buyer and/or end users' responsibility to review our complete Terms and Conditions of Sale located on our web sites at: www.novaflex.com | www.z-flex.com | www.flexmaster.com.

10.2020

IN USA

North Carolina

449 Trollingwood Road
Haw River, NC 27258
tel (336)578-2161
fax (336)578-5554
800-334-4270

New Jersey

1024 Industrial Drive
West Berlin, NJ 08091
tel (856)768-2275
fax (856)768-2385
800-225-0215

Indianapolis

7812 Moller Road
Indianapolis, IND 46268
tel (317)334-1444
fax (317)334-1535
800-526-6288

IN CANADA

Ajax, Ontario

555 Beck Crescent
Ajax, ON L1Z 1C9
tel (905)686-5200
fax (905) 686-8349
800-563-3539

IN U.K.

Bromborough, Wirral

18 Plantation Park 2, Power Road
Bromborough, Wirral UK CH62 3QT
tel 44(0)151-334-0873
fax 44(0)151-334-7145
www.novaflex.co.uk Email: sales@novaflex.co.uk