

Novaflex®

Water Removal & Hydrant Services

Novaflex 2160

Water Removal and Hydrant Services

Premium quality heavy duty hose designed for suction and discharge applications commonly found in water removal and hydrant service on fire trucks.



Specifications

Tube: SBR
Reinforcement: Multiple plies of polyester tire cord with helix
Cover: Smooth SBR
Length: Available in specific lengths with cuff ends - price on application
Temperature Range: -40° to 180°F
Meets or exceeds NFPA #189 & 1901 requirements

Part No.	I.D.	O.D.	Plies	WP psi	Min Order Lgth	WT LBS/FT
2160BS-02500-00	2	3.25	2	150	100'	2.46
2160BS-03000-00	2½	3.687	2	150	100'	2.88
2160BS-04000-00	3	4.25	2	150	50'	3.77
2160BS-04500-00	4	4.687	4	150	50'	5.16
2160BS-05000-00	5	5.75	4	150	50'	5.77
2160BS-06000-00	6	6.75	4	150	50'	7.03

Novaflex 2161

Water Removal and Hydrant Services

Premium quality heavy duty hose designed for suction and discharge applications commonly found in water removal and hydrant service on fire trucks.



Specifications

Tube: SBR
Reinforcement: Multiple plies of polyester tire cord with helix
Cover: Corrugated black EPDM cover
Length: up to 100 ft
Temperature Range: -40° to 180°F
Hose comes with 6" cuffed ends. Meets or exceeds NFPA #189 & 1901 requirements

Part No.	I.D.	O.D.	Plies	WP psi	Min Qty	WT LBS/FT
2161BS-02500-00	2	3.04	2	150	4	2.42
2161BS-03000-00	2½	3.54	2	150	4	2.9
2161BS-04000-00	3	4.54	2	150	2	3.47
2161BS-04500-00	4	4.687	4	159	2	5.2
2161BS-05000-00	5	5.54	4	150	2	5.88
2161BS-06000-00	6	6.58	4	150	2	7.36

All products are warranted to be free from all defects in material and workmanship. It is impossible to test all products under all conditions to which they might be subjected in the field. It is therefore the buyer and/or end users' responsibility to test all products under the conditions that duplicate the service conditions prior to installation. All improvements, all specifications are subject to change without prior notice. It is the buyer and/or end users' responsibility to review our complete **Terms and Conditions of Sale** located on our web sites at: www.novaflex.com / www.z-flex.com / www.flexmaster.com.

05.2019

IN USA

North Carolina

449 Trollingwood Road
Haw River, NC 27258
tel (336)578-2161
fax (336)578-5554
800-334-4270

New Jersey

1024 Industrial Drive
West Berlin, NJ 08091
tel (856)768-2275
fax (856)768-2385
800-225-0215

Indianapolis

7812 Moller Road
Indianapolis, IND 46268
tel (317)334-1444
fax (317)334-1535
800-526-6288

IN CANADA

Ajax, Ontario

555 Beck Crescent
Ajax, ON L1Z 1C9
tel (905)686-5200
fax (905) 686-8349
800-563-3539

IN U.K.

Bromborough, Wirral

18 Plantation Park 2, Power Road
Bromborough, Wirral UK CH62 3QT
tel 44(0)151-334-0873
fax 44(0)151-334-7145
www.novaflex.co.uk Email: sales@novaflex.co.uk